

MODEL 250 H.O.-V6

SPECIFICATIONS



Model	a. E250DHL b. E250HSL c. E250DHX
Shaft Length mm (in) / Color	a. 508 (20") Blue b. 508 (20") White c. 635 (25") White
Weight kg (lbs)	a. / b. 231 (509) c. 234 (515)
Engine Type	Loop Charged V6 90° E-TEC Direct Injection
Bore x Stroke mm (in)	98 x 76 (3.854 x 3.000)
Displacement cc (cu in)	3441 (210)
Ignition System	IDI Fast Rise Inductive Ignition
Starter	Electric
Trim Method	FasTrak™ Power Trim and Tilt
Propshaft kilowatts (HP)*	Factory Tuned for High Performance
Full Throttle Operating Range	4500-6000 RPM
Gear Ratio	1.71:1 High Speed
Fuel Induction	E-TEC Direct Fuel Injection with stratified low RPM combustion mode
Alternator	Variable Voltage Computer Controlled 133 Amp** / 1800 watt output with Regulator
Cooling	Pressure and Temperature Controlled Water Cooled
Steering	Remote
Limited Warranty	3 Years Non-Declining
Emissions Compliance	EPA CARB 3 STAR European Union



* Power Ratings: Evinrude® outboards are power rated in accordance with NMMA procedure using the International Council of Marine Industry Associates (ICOMA) standard 28/83.

** 133 Amp current calculated at 13.5 V. Net dedicated battery charging power output is 50 Amp.