

MODEL 50 SPECIFICATIONS



| | |
|-------------------------------|--|
| Model | a. E50DPL b. E50DSL c. E50DTL |
| Shaft Length mm (in) / Color | a. / c. 508 (20") Blue b. 508 (20") White |
| Weight kg (lbs) | a. / b. 109 (240) c. 113 (251) |
| Engine Type | Inline 2-cylinder E-TEC Direct Injection |
| Bore x Stroke mm (in) | 91 x 66 (3.600 x 2.588) |
| Displacement cc (cu in) | 863 (52.7) |
| Ignition System | IDI Fast Rise Inductive Ignition |
| Starter | Electric |
| Trim Method | Power Trim and Tilt |
| Propshaft kilowatts (HP)* | 37 kw (50 HP) @ 5750 RPM |
| Full Throttle Operating Range | 5500-6000 RPM |
| Gear Ratio | 2.67:1 |
| Fuel Induction | E-TEC Direct Fuel Injection with stratified low RPM combustion mode |
| Alternator | Variable Voltage Computer Controlled 81 Amp** / 1100 watt output with Regulator |
| Cooling | Pressure and Temperature Controlled Water Cooled |
| Steering | a. / b. Remote c. Tiller Standard |
| Limited Warranty | 3 Years Non-Declining |
| Emissions Compliance | EPA CARB 3 STAR European Union |



* Power Ratings: Evinrude® outboards are power rated in accordance with NMMA procedure using the International Council of Marine Industry Associates (ICOMA) standard 28/83.

** 81 Amp current calculated at 13.5 V. Net dedicated battery charging power output is 25 Amp.