

# EVINRUDE®



# 3.5 HP

## SPECIFICATIONS

ENGINE TYPE	1-CYLINDER/4-STROKE
BORE X STROKE MM (IN)	55 X 36 (2.17 X 1.42)
DISPLACEMENT CC (CU IN)	85.5 (5.2)
GEAR RATIO	2.15:1
FULL THROTTLE RPM RANGE	5,000 - 6,000 RPM
WEIGHT KG (LBS)*	18 (41)*
STARTING	MANUAL
OIL TYPE	NMMA CERTIFIED FC-W® 4-STROKE OIL SAE 10W-30/40 (SF, SG, SH, SJ)
OIL CAPACITY ML (FL. OZ.)	300 (10)
FUEL TANK L	INTEGRAL TANK 1
PROPELLER SELECTION RANGE CM(IN)	11.43-17.78 (4.5-7)
ALTERNATOR OUTPUT	N/A
STEERING	TILLER HANDLE
TRIM METHOD	MANUAL TILT
SHAFT LENGTH MM (IN)	381 (15), 508 (20)
WARRANTY	3-YEAR, NON-DECLINING
EMISSIONS COMPLIANCE	CARB 3 STAR

\* Weight based on lightest model.

# EVINRUDE®



# 4 HP

## SPECIFICATIONS

ENGINE TYPE	1-CYLINDER/4-STROKE
BORE X STROKE MM (IN)	59 X 45 (2.32 X 1.77)
DISPLACEMENT CC (CU IN)	123 (7.5)
GEAR RATIO	2.15:1
FULL THROTTLE RPM RANGE	4,500 - 5,500 RPM
WEIGHT KG (LBS)*	26 (57)
STARTING	MANUAL
OIL TYPE	NMMA CERTIFIED FC-W® 4-STROKE OIL SAE 10W-30/40 (SF, SG, SH, SJ)
OIL CAPACITY ML (FL. OZ.)	450 (15)
FUEL TANK L	INTEGRAL TANK 1.1
PROPELLER SELECTION RANGE CM (IN)	15.24-22.86 (6-9)
ALTERNATOR OUTPUT	OPTIONAL ACCESSORY: 12V, 60W, 5A
STEERING	TILLER HANDLE
TRIM METHOD	MANUAL TILT
SHAFT LENGTH MM (IN)	381 (15), 508 (20)
WARRANTY	3-YEAR, NON-DECLINING
EMISSIONS COMPLIANCE	CARB 3 STAR

\* Weight based on lightest model.

# EVINRUDE®



# 6 HP

## SPECIFICATIONS

ENGINE TYPE	1-CYLINDER/4-STROKE
BORE X STROKE MM (IN)	59 X 45 (2.32 X 1.77)
DISPLACEMENT CC (CU IN)	123 (7.5)
GEAR RATIO	2.15:1
FULL THROTTLE RPM RANGE	5,000-6,000 RPM
WEIGHT KG (LBS)*	25 (55)
STARTING	MANUAL
OIL TYPE	NMMA CERTIFIED FC-W® 4-STROKE OIL SAE 10W-30/40 (SF, SG, SH, SJ)
OIL CAPACITY ML (FL. OZ.)	450 (15)
FUEL TANK L	INTERNAL FUEL TANK MODELS: 1.1 INTEGRAL TANK
PROPELLER SELECTION RANGE CM (IN)	15.24-22.86 (6-9)
ALTERNATOR OUTPUT	OPTIONAL ACCESSORY: 12V, 60W, 5A (STANDARD ON 25" SHAFT MODEL)
STEERING	TILLER HANDLE
TRIM METHOD	MANUAL TILT
SHAFT LENGTH MM (IN)	381 (15), 508 (20), 635 (25)
WARRANTY	3-YEAR, NON-DECLINING
EMISSIONS COMPLIANCE	CARB 3 STAR

\* Weight based on lightest model.

# EVINRUDE®



# 9.8 HP

## SPECIFICATIONS

ENGINE TYPE	2-CYLINDER/4-STROKE
BORE X STROKE MM (IN)	(55 X 44) 2.17 X 1.73
DISPLACEMENT CC (CU IN)	209 (12.8)
GEAR RATIO	2.08:1
FULL THROTTLE RPM RANGE	5,000-6,000 RPM
WEIGHT KG (LBS)*	37 (81.5)
STARTING	ELECTRIC OR MANUAL
OIL TYPE	NMMA CERTIFIED FC-W® 4-STROKE OIL SAE 10W-30/40 (SF, SG, SH, SJ)
OIL CAPACITY ML (FL. OZ.)	800 (27)
FUEL TANK L	12 SEPARATE FUEL TANK
PROPELLER SELECTION RANGE CM(IN)	16.51-24.13 (6.5-9.5)
ALTERNATOR OUTPUT	OPTIONAL ACCESSORY: 12V, 80W, 6A (STANDARD ON ELECTRIC START MODELS)
STEERING	REMOTE CONTROL OR TILLER HANDLE
TRIM METHOD	MANUAL OR POWER TILT
SHAFT LENGTH MM (IN)	381 (15), 508 (20), 635 (25)
WARRANTY	3-YEAR, NON-DECLINING
EMISSIONS COMPLIANCE	CARB 3 STAR

\* Weight based on lightest model.

# EVINRUDE®



# 15 HP

## SPECIFICATIONS

ENGINE TYPE	2-CYLINDER/4-STROKE
BORE X STROKE MM (IN)	61 X 60 (2.4 X 2.36)
DISPLACEMENT CC (CU IN)	351 (21.41)
GEAR RATIO	2.15:1
FULL THROTTLE RPM RANGE	5,000-6,000 RPM
WEIGHT KG (LBS)*	52 (114.4)
STARTING	ELECTRIC OR MANUAL
OIL TYPE	NMMA CERTIFIED FC-W® 4-STROKE OIL SAE 10W-30/40 (SF, SG, SH, SJ)
OIL CAPACITY ML (QT)	1000 (1)
FUEL TANK L	12 SEPARATE FUEL TANK
PROPELLER SELECTION RANGE CM (IN)	15.24-25.4(6-10)
ALTERNATOR OUTPUT	OPTIONAL ACCESSORY: 12V, 145W, 12A (STANDARD ON ELECTRIC START MODELS)
STEERING	REMOTE CONTROL OR TILLER HANDLE
TRIM METHOD	MANUAL OR POWER TILT
SHAFT LENGTH MM (IN)	381 (15), 508 (20)
WARRANTY	3-YEAR, NON-DECLINING
EMISSIONS COMPLIANCE	CARB 3 STAR

\* Weight based on lightest model.